

EDANUSA

www.edanusa.com

DUS 3



■ **Digital Ultrasonic Diagnostic Imaging System**

Care for Health



DUS 3

Technical Specifications

Convex array:
C363-1



Micro-convex array:
C321-1



Endovaginal:
E611-1



Convex array:
C341



Linear array:
L741



Endorectal:
E741



General:

Imaging mode: B, B+B, 4B, B+M, M
 Gray scales: 256
 Display: 10" non-interlaced
 Transducer frequency:
 2.0-10.0 MHz
 Transducer connector:
 1 (standard) 2 (optional)
 Beam-forming: Digital Beam-forming
 Dynamic Receiving Focusing
 Real-time Dynamic Aperture
 Dynamic Frequency Scanning
 Dynamic Apodization
 Tissue Harmonic Imaging
 Tissue Specific Imaging
 Scanning angle:
 from 30 to 155 degree (depending on transducers)
 Scanning depth (mm):
 from 20 to 250 (depending on transducers)

Imaging Processing:

Pre-processing: Dynamic range
 Edge enhancement
 Frame correlation
 Line correlation
 Smooth
 AGC
 4-segment TGC adjustment
 IP (Image Process)
 Post-processing: Gray map
 Gamma correction
 Rejection
 Black / white reverse
 Left / right reverse
 Up / down reverse
 Image rotation at 90 degree interval

Functions:

Cine loop: 128 frames bidirectional cine-loop
 Zoom: X1.0, X1.2, X1.4, X1.6, X2.0, X2.4,
 X3.0, X4.0 in distance
 Storage media:
 Built-in Flash, External USB-Memory stick
 Storage: 56 MB permanent image
 Body mark: >130 types
 Transducer auto-detection
 16-segment acoustic power output adjustment

Measurement & Calculation:

B-mode: distance, circumference, area, volume,
 angle, ratio, %stenosis
 M-mode: distance, time, velocity, heart rate (2 cycles), slope
 Software packages:
 abdomen, gynecology, obstetrics, urology,
 small parts, cardiology, orthopedics

Display:

Date, Time, Probe Name, Probe Frequency, Frame Rate,
 Patient Name, Patient ID, Hospital Name, Measurement Values,
 Body Marks, Annotation, Probe Position, Full-image-region edit

Others:

Peripheral port: Video output X1
 VGA output port X1
 USB port X2
 DICOM3.0 X1 (optional)
 Power supply: 100V-240V ~ 50Hz/60Hz
 Dimensions: 353mm(W) X 315mm(L) X 253mm(H)
 Net weight: 11.5 kg

Standard Configurations:

DUS 3 main unit
 10" non-interlaced monitor
 One transducer connector
 128 frames cine loop memory
 56MB built-in image storage
 Two USB ports
 Measurement & calculation software packages
 Convex array transducer:
 C361-1 (2.0/3.0/4.0/5.0/6.0 MHz)
 One cable holder

Options:

Linear array transducer:
 L741 (6.0/7.0/8.0/9.0/10.0 MHz)
 Endorectal transducer:
 E741 (6.0/7.0/8.0/9.0/10.0 MHz)
 Endovaginal transducer:
 E611-1 (4.5/5.5/6.5/7.5/8.5 MHz)
 Convex array transducer:
 C341 (2.0/3.0/4.0/5.0/6.0 MHz)
 Micro-convex array transducer:
 C321-1 (4.0/5.0/6.0 MHz)
 Two transducer connectors
 Video printer
 Laser printer
 Inkjet printer
 Biopsy guide
 DICOM 3.0
 Footswitch
 Mobile trolley
 Hand carried bag

EDAN USA

4901 Morena Blvd., Suite 505
 San Deigo, CA 92117
 Tel: 888.850.4597



Distributor: